

## FISA TEHNICA – BANDA ADEZIVA DIN ALUMINIU GOFRAT

ALUMINIU	tip 1200, monolucid, gofrat
ADEZIV	sintetic
LINER	hartie siliconata
GROSIME	30 sau 50µm      EN 546/3

In tabelul urmatoar sunt cuprinse valorile nominale, valorile minime si maxime de toleranta

<b>Grosime</b>	<b>30 microni</b>	<b>50 microni</b>
Minim	28.8	48.0
Maxim	31.2	52.0

TEMPERATURA DE APLICARE	intre +10°C si +35°C
TEMP DE LUCRU ADEZIV	intre -20°C si +75°C
REZISTENTA LA FOC	clasa 1 (referitor la material)
ALUNGIREA	7-10%
REZISTENTA LA RUPERE	1,2 N/cm
ADERENTA PE OTEL (Peel)	400 N/cm
ADERENTA PROPRIE	450 N/cm
DIMENSIUNE CUTIE	300 x 300 x 300mm
NR. CUTII PE PALET	48

<b>COD PRODUS</b>	<b>GROSIME</b>	<b>LATIME</b>	<b>LUNGIME</b>	<b>BUC/CUTIE</b>
<b>HMH50G30-50</b>	<b>30µ</b>	<b>50mm</b>	<b>50m</b>	<b>24</b>
<b>HMH75G30-50</b>	<b>30µ</b>	<b>75mm</b>	<b>50m</b>	<b>16</b>
<b>HMH100G30-50</b>	<b>30µ</b>	<b>100mm</b>	<b>50m</b>	<b>12</b>
<b>HMH50G50-50</b>	<b>50µ</b>	<b>50mm</b>	<b>50m</b>	<b>24</b>
<b>HMH75G50-50</b>	<b>50µ</b>	<b>75mm</b>	<b>50m</b>	<b>16</b>
<b>HMH100G50-50</b>	<b>50µ</b>	<b>100mm</b>	<b>50m</b>	<b>12</b>