

FISA TEHNICA – BANDA DIN ALUMINIU RANFORSAT

ALUMINIU	tip 1200, monolucid
ADEZIV	Sintetic
LINER	hartie siliconata
GROSIME	30 sau 40 μm EN 546/3

In tabelul urmator sunt cuprinse valorile nominale, valorile minime si maxime de toleranta

Grosime	30 microni	40 microni
Minim	28.8	38.4
Maxim	31.2	41.6

TEMPERATURA DE APLICARE	intre +10°C si +35°C	
TEMP DE LUCRU ADEZIV	intre -20°C si +75°C	
REZISTENTA LA FOC	clasa 0 (referitor la material)	B.S. 476 PART 7
ALUNGIREA	3-5% (30 μ), 5-7% (40 μ)	ASTM E 345
REZISTENTA LA RUPERE	1,2 N/cm	ASTM E 345
ADERENTA PE OTEL (Peel)	400 N/cm	PSTC n.1
ADERENTA PROPRIE	450 N/cm	PSTC n.1
DIMENSIUNE CUTIE	280 x 280 x 300mm	
NR. CUTII PE PALET	48	

COD PRODUS	GROSIME	LATIME	LUNGIME	BUC/CUTIE
HMH50R30-50	30 μ	50mm	50m	24
HMH75R30-50	30 μ	75mm	50m	16
HMH100R30-50	30 μ	100mm	50m	12
HMH50R40-50	40 μ	50mm	50m	24
HMH75R40-50	40 μ	75mm	50m	16
HMH100R40-50	40 μ	100mm	50m	12