

FISA TEHNICA – GARNITURA ADEVIVA DIN POLIETILENA CLASA 1

DENSITATE	33 kg/m ³	
CULOARE	gri deschis	
GROSIME	3 sau 6mm	ISO 1923

In tabelul urmatoar sunt cuprinse valorile nominale, valorile minime si maxime de toleranta

Grosime	3mm	6mm
Minim	2.6	5.4
Maxim	3.5	6.6

TEMPERATURA DE APLICARE	intre +10°C si 35°C	
TEMP DE LUCRU A ADEZIVULUI	intre -20°C si +75°C	
COMPORTAMENT LA FOC	clasa 1 (conform CSE RF2/75, RF3/77)	
CONDUCTIBILITATEA TERMICA	la temp medie de 40°C $\lambda = 0,0372$ W/mK	
FACTOR DE REZISTENTA LA DIFUZIA VAPORILOR DE APA	$\mu = 2192$	DIN 52615
REZISTENTA LA COMPRESIE	190g/cm ²	la 10%
ABSORTIA DE APA	< 3% volumetric (dupa 28 de zile)	
ADEZIV	sintetic	
LINER	hartie siliconata	
DIMENSIUNE CUTIE	560 x 560 x 500mm	
NR CUTII PE PALET	16 cutii	

COD PRODUS	GROSIME	LATIME	LUNGIMEA	ROLE/CUTIE	ML/CUTIE
GPECL1-3-10	3mm	10mm	20m	200	4000
GPECL1-6-10	6mm	10mm	10m	200	2000
GPECL1-3-15	3mm	15mm	20m	132	2640
GPECL1-6-15	6mm	15mm	10m	132	1320
GPECL1-3-20	3mm	20mm	20m	100	2000
GPECL1-6-20	6mm	20mm	10m	100	1000